RB25



10W Digital/Analog Handheld Walkie Talkie

Feature:

10W digital mode, call quality, strong anti-interference, and more obvious confidentiality performance.



10W Digital/Analog Handheld Walkie Talkie

General

Product number: **RB25**

UHF: 400-480MHz Frequency range:

Channel number: 32CH

25KHz\12.5KHz Channel spacing:

Standby current: ≤20mA

-10℃~+50℃ Operating temperature range:

The antenna impedance: 50Ω

Rated Voltage: 7.4V

Transmitter

High: 10W Low: 1W Rf power:

Modulation restriction: ≤2.5kH

Adjacent channel selectivity: ≥60dB

Spurious radio frequency: ≤7.5µW

Emission current: ≤2.5A

RECEIVER

Reference sensitivity: width≤0.25uV narrow≤0.35uV

Audio power: ≥300mW

Waiting current: ≤20mA

width≤0.20uV narrow≤0.25uV Turn on sensitivity:

Receive current: ≤410 mA

Package includes:

- 1 x Host
- 1 x Battery
- 1 x Lanyard
- 1 x Manual
- 1 x Back clip
- 1 x USB-Charger



CE F© RoHS



Shenzhen Retevis Technology Co.,Ltd.

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli 6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com E-mail: kam@retevis.com Facebook: facebook.com/retevis

